



FORMED CASE SIZE

STANDARD FORMED CASE RANGE	
MINIMUM	MAXIMUM
LENGTH	25.0" (635)
WIDTH	25.0" (635)
DEPTH	14.0" (355)

UTILITY REQUIREMENTS

AIR REQUIREMENTS: 3.788 SCF/CYCLE @ 80 PSI (0.073 m³/CYCLE @ 551.2 KPa)
 1.957 SCF/CYCLE @ 80 PSI (0.055 m³/CYCLE @ 551.2 KPa) (WITH OPTIONAL SERVO H FOLD DRIVE)
 ELECTRICAL REQUIREMENTS: 480 V/3 PHASE/60 Hz STANDARD
 FULL LOAD AMPS: 15.0 AMPS
 DISCONNECT SIZE: 30 AMP

POWER REQUIREMENTS PROVIDED ARE FOR A BASE MACHINE AND CUSTOM OPTIONS MAY RESULT IN CHANGES.

MACHINE WEIGHT (APPROXIMATE): 7,100 LBS. (3,217 Kg)

MACHINE SPEED: SEE ORDER SPECIFICATION

PROPRIETARY
 NEITHER THIS DOCUMENT NOR THE
 INFORMATION CONTAINED THEREIN
 MAY BE REPRODUCED OR DISCLOSED
 TO ANYONE WITHOUT THE WRITTEN
 PERMISSION OF R.A. PEARSON CO.

DATE	REVISION	ECN NO.	REV. BY	CHKD BY
3/25/18	PV 1000 WAS PV700, UP-DATE ELEC UTILITY INFO		K.A.	
6/3/16	SHOW 3 AND 6 FOOT INCLINED CONVEYOR ELEV. RANGES		K.A.	
9/24/14	SHOW STRETCHED FRAME (STRETCHED 12 IN.)		K.A.	
9/9/14	CHANGED AIR INLET FROM 3/4 TO 1 INCH		K.A.	
4/16/14	REDRAWN WITH NEW DESIGN, NEW MODEL NUMBER		K.A.	
12/13/13	SHOW GLUE UNIT IN PLAN VIEW		K.A.	
11/26/13	CORRECT LENGTH AND WIDTH CALLOUT ON CASE ISO VIEW		K.A.	
10/30/13	SHOW MORE COMMON BODY WRAP IN SET UP SEQUENCE		K.A.	

PRELIMINARY
 (ALL DIMENSIONS ARE APPROXIMATE
 AND MAY VARY WITH FINAL DESIGN)

2' - 2 7/16"
 672
 DIMENSIONS ARE IN
 FOOT FRACTION INCH
 OVER MILLIMETERS.

TITLE		DR.		DWG NO.	
BF25-GH BLISS FORMER 2 PIECE H DIVIDER		K.A.	10/2/13	721003	
CHK.		APP.		SCALE	SHEET

PEARSON
 PACKAGING SYSTEMS
 8120 WEST SUNSET HIGHWAY
 SPOKANE, WASHINGTON 99224
 WWW.PEARSONPKS.COM