


AIR REQUIREMENTS: 1.038 SCF/CYCLE @ 80 PSI (0.0290m³ PER CYCLE @ 551.2 KPa) ELECTRICAL REQUIREMENTS: 230/460 VOLTS, 3 PHASE, 60 Hz STANDARD

FULL LOAD AMPS - 25.0 Amps DISCONNECT SIZE - 30 Amp

POWER REQUIREMENTS PROVIDED ARE FOR A BASE MACHINE AND CUSTOM OPTIONS MAY RESULT IN CHANGES.

MACHINE WEIGHT: APPROX. 2,000 LBS. (901 Kg.)


SPEED CAPACITY: CASE ERECTOR IS CAPABLE OF UP TO 25 CPM.




DOUBLE POINT SCORING

THE STYLE AND QUALITY OF SCORING CAN EFFECT THE OPERATION AND PERFORMANCE OF THE CASE ERECTOR. DOUBLE POINT SCORING BE USED. (SEE SKETCH ABOVE) IN ORDER TO MAXIMIZE THE CONSISTENCY OF OPERATION OF YOUR MACHINE

MACHINE SHOWN RUNS LH CASES





KNOCK-DOWN CASE DESCRIPTION:

CORRUGATED SIZE RANGE


ERECTED CASE SIZE


ERECTED CASE SIZE						
CASE	LENGTH	WIDTH	DEPTH	OPEN DEPTH		
MINIMUM	8.00 (203)	5.50 (140)*	3.00 (76)	6.0 (152)		
MAXIMUM	24.00 (610)	16.00 (406)	18.50 (470)	21.00 (533)		

^{*} CASE WIDTH VARIES DEPENDING ON CASE STYLE.

KNOCKDOWN CASE SIZES (IN)

	KDL	KDW	FLAP	
MINIMUM	13.00 (330)	8.00 (203)	2.50 (64)	
MAXIMUM	40.00 (1016)	29.00 (737)	8.00 (203)	





PRELIMINARY

(ALL DIMENSIONS ARE APPROXIMATE AND MAY VARY WITH FINAL DESIGN)

===========
PROPRIETARY
NEITHER THIS DOCUMENT NOR THE
INFORMATION CONTAINED THERIN
MAY BE REPRODUCED OR DISCLOSED
TO ANYONE WITHOUT THE WRITTEN
PERMISSION OF R.A. PEARSON CO.

DATE	REVISION	ECN NO.	REV.	CHKD	
6/5/15	ADD 10 FOOT MAGAZINE EXTENSION		K.A.		,
5/24/16	DELETE 6FTADDITIONAL MAG. OPTION		K.A.		F
11/29/17	SHOW OPTIONAL CONFIGURATION TEXT		K.A.		
3/24/18	UP-DATE ELEC UTILITY INFO, PV 1000 WAS 700		K.A.		
1/15/20	SHOW STREAMLINED 30 DAY CONFIGURATION		K.A.		

2' - 2 7/16" 672 CE25-G CASE ERECTOR HOT MELT GLUE SEAL DIMENSIONS ARE IN FOOT FRACTION INCH 638032R-3 OVER MILLIMETERS. SHEET