



STANDARD ADJUSTMENT RANGE		
	MINIMUM	MAXIMUM
LENGTH	6.0" (152)	24.0" (610)
WIDTH	4.5" (114)	16.0" (407)
DEPTH	3.0" (76)	18.5" (470)

**UTILITY REQUIREMENTS**  
 AIR REQUIREMENTS: 0.0005m<sup>3</sup>/CYCLE @ 551.2 KPa (0.016 SCF/CYCLE @ 80PSI)  
 ELECTRICAL REQUIREMENTS: 110 VAC SINGLE PHASE, 7.7 AMPS  
 FULL LOAD AMPS - 6 AMPS  
 DISCONNECT SIZE - 16 AMP

**NOTE: UTILITIES INFO LISTED IS PRELIMINARY AND IS SUBJECT TO CHANGE WITH FINAL DESIGN**

MACHINE WEIGHT (APPROXIMATE: ) \_\_\_\_\_ 700 LBS (318Kg)  
 MACHINE SPEED: 15 CPM

**PRELIMINARY**  
 (ALL DIMENSIONS ARE APPROXIMATE AND MAY VARY WITH FINAL DESIGN)

PROPRIETARY  
 NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED THEREIN MAY BE REPRODUCED OR DISCLOSED TO ANYONE WITHOUT THE WRITTEN PERMISSION OF R.A. PEARSON CO.

DATE	REVISION	ECN NO.	REV. BY	CHKD BY
10/8/20	TAPE HEAD UPDATE	SFC		

2' - 2 7/16" 672

DIMENSIONS ARE IN FOOT FRACTION INCH OVER MILLIMETERS.

**PEARSON**  
 4125 WEST SUNSET HIGHWAY  
 SPOKANE, WASHINGTON 99224  
 WWW.PEARSONPKG.COM

TITLE  
**CS15-29T CASE SEALER**

DR.	SFC	10/7/20	DWG NO.
CHK.			D624540L-3
APP.			SCALE
			SHEET