



STANDARD ADJUSTMENT RANGE		
	MINIMUM	MAXIMUM
LENGTH	12"(305)	30"(762)
WIDTH	8"(203)	24"(610)
DEPTH	6"(152)	26"(660)
OPEN DEPTH	10"(254)	38"(965)
FLAP LENGTH	4"(102)	12"(305)

UTILITY REQUIREMENTS
 AIR REQUIREMENTS: 0.197 SCF/CYCLE @ 80 PSI (0.006m³/CYCLE @ 551.2 KPa)
 ELECTRICAL REQUIREMENTS: 460 V/3 PHASE/60 Hz STANDARD
 FULL LOAD AMPS - 5.1 AMPS
 DISCONNECT SIZE - 30 AMP

NOTE: UTILITIES INFO LISTED IS PRELIMINARY AND IS SUBJECT TO CHANGE WITH FINAL DESIGN

MACHINE WEIGHT (APPROXIMATE:) 2,200 LBS (1,000 Kg)

MACHINE SPEED: SEE ORDER SPECIFICATION

PROPRIETARY
 NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED THEREIN MAY BE REPRODUCED OR DISCLOSED TO ANYONE WITHOUT THE WRITTEN PERMISSION OF R.A. PEARSON CO.

DATE	REVISION	EDN NO.	REV. BY	CHKD BY
11/29/17	SHOW OPTIONAL CONFIGURATION TEXT	-1	K.A.	
12/12/14	UP-DATED PNEUMATIC UTILITY CALLOUTS		K.A.	
6/3/14	PV +6 7 INCH HMI WAS PUSHBUTTON STATION		K.A.	
6/26/13	ADD FLAP LENGTH TO CASE RANGE CHART		K.A.	
6/4/08	SHOW 36X36 ENCLOSURE (WAS 30X30)		K.A.	

2' - 2 7/16" 672

DIMENSIONS ARE IN FOOT FRACTION INCH OVER MILLIMETERS.

PEARSON
 PACKAGING SYSTEMS

8125 WEST SUNSET HIGHWAY
 SPOKANE, WASHINGTON 99224
 WWW.PEARSONPKG.COM

TITLE
CS25-20T
INTERMEDIATE SIZE CASE SEALER

DR.	D.N.	9/28/07	DWG NO.	D615366-1
CHK.			SCALE	
APP.			SHEET	