



STANDARD ADJUSTMENT RANGE		
	MINIMUM	MAXIMUM
LENGTH	12"(305)	30"(762)
WIDTH	8"(203)	24"(610)
DEPTH	6.0"(152)	26"(660)
OPEN DEPTH	10"(254)	38"(965)
FLAP LENGTH	4"(102)	12"(305)

UTILITY REQUIREMENTS

AIR REQUIREMENTS: 0.178 SCF/CYCLE @ 80 PSI (0.005m³ / CYCLE @ 551.2 KPa)
 WITH OPTIONAL PNEUMATIC CASE METERING: 0.213 SCF/CYCLE @ 80 PSI (0.006m³ / CYCLE @ 551.2KPa)

ELECTRICAL REQUIREMENTS: 460 V/3 PHASE/60 Hz STANDARD
 FULL LOAD AMPS - 16.0 AMPS
 DISCONNECT SIZE - 30 AMP

NOTE: UTILITIES INFO LISTED IS PRELIMINARY AND IS SUBJECT TO CHANGE WITH FINAL DESIGN

MACHINE WEIGHT (APPROXIMATE): 2,385 LBS (1,084 Kg)

MACHINE SPEED: SEE ORDER SPECIFICATION FOR YOUR MACHINE SPEED

PROPRIETARY
 NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED THEREIN MAY BE REPRODUCED OR DISCLOSED TO ANYONE WITHOUT THE WRITTEN PERMISSION OF R.A. PEARSON CO.

DATE	REVISION	EDN NO.	REV. BY	CHKD BY
12/12/14	UP-DATED PNEUMATIC UTILITY CALLOUTS		K.A.	
6/3/14	PV +6 7 INCH HMI WAS PUSHBUTTON STATION		K.A.	
6/26/13	ADD FLAP LENGTH TO CASE RANGE CHART		K.A.	
6/4/08	SHOW 36X36 ENCLOSURE (WAS 30X30)		K.A.	

2' - 2 7/16" 672			
DIMENSIONS ARE IN FOOT FRACTION INCH OVER MILLIMETERS.		TITLE CS25-20G INTERMEDIATE SIZE CASE SEALER	
DR.	D.N.	9/28/07	DWG NO.
CHK.			D653209-1
APP.			SCALE
			SHEET

8125 WEST SUNSET HIGHWAY
 SPOKANE, WASHINGTON 99224
 WWW.PEARSONPKG.COM