

Technical Data Sheet

Industrial Grade Hot Melt Tape Premium

PearsonTape H-2030 is an industrial grade packaging tape for carton sealing, splicing, bundling, and other heavy packaging applications. This product offers high adhesive power, ideal for shipping purposes and heavy handling.

Technical Specifications

Available Colors	Clear, Tan
Backing BOPP	1.16 mils / 0.029 mm
Adhesive	Synthetic Rubber and Resins
Total Thickness	2.03 mils / 0.051 mm
Adhesion to Steel	56 oz/in. / 60 N/100mm
Tensile Strength	26 lbs/in. / 455 N/100mm
Elongation at Break	165 %
Service Temp.	Min: 30°F (-2°C) Max: 140°F (60°C)
Application Temp.	Min: 50°F (10°C) Max: 110°F (43°C)
Available Options	W: 48 mm / L: 914 m Part No: 305914 W: 72 mm / L: 914 m Part No: 305915

Performance Features

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Excellent edge tear and split resistance
- Aggressive high tack adhesive with excellent holding powers

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or the Manufacturer's Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

All materials used in the above referenced product conform to the requirements set forth by FDA 21CFR177.1520 (film) and 21CFR175.105 (adhesive) and comply with environmental considerations of ASTM D 1974-14.

Country of Origin: North America