

## Technical Data Sheet

**Industrial Grade Hot Melt Tape Superior Performance** PearsonTape H-2830 is an industrial grade packaging tape designed for carton sealing, splicing, bundling, and other ultra demanding packaging applications. PearsonTape H-2830 offers superior adhesive power ideally suited for the heaviest applications.

### Technical Specifications

Available Colors	Clear, Tan
Backing BOPP	1.97 mils / 0.050 mm
Adhesive	Synthetic Rubber and Resins
Total Thickness	2.83 mils / 0.072 mm
Adhesion to Steel	56 oz/in. / 60 N/100mm
Tensile Strength	45 lbs/in. / 787 N/100mm
Elongation at Break	200 %
Service Temp.	Min: 30°F (-2°C)   Max: 140°F (60°C)
Application Temp.	Min: 50°F (10°C)   Max: 110°F (43°C)
Available Options	W: 48 mm / L: 914 m   Part No: 305918 W: 72 mm / L: 914 m   Part No: 305919

### Performance Features

- Adheres instantly to corrugated, paper, film and a number of surfaces
- Excellent edge tear and split resistance
- Aggressive high tack adhesive with excellent holding powers

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or the Manufacturer's Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

All materials used in the above referenced product conform to the requirements set forth by FDA 21CFR177.1520 (film) and 21CFR175.105 (adhesive) and comply with environmental considerations of ASTM D 1974-14.

Country of Origin: North America