



STANDARD ADJUSTMENT RANGE		
	MINIMUM	MAXIMUM
LENGTH	6.0" (152)	24.0" (610)
WIDTH	4.5" (114)	16.0" (407)
DEPTH	3.0" (76)	18.5" (470)

UTILITY REQUIREMENTS

AIR REQUIREMENTS: 0.0005m³/CYCLE @ 551.2 KPa (0.016 SCF/CYCLE @ 80PSI)

ELECTRICAL REQUIREMENTS: 460 VAC 3 PHASE
 FULL LOAD AMPS - 4.8 AMPS
 DISCONNECT SIZE - 30 AMP

NOTE: UTILITIES INFO LISTED IS PRELIMINARY AND IS SUBJECT TO CHANGE WITH FINAL DESIGN

MACHINE WEIGHT (APPROXIMATE:) _____ 700 LBS (318Kg)

MACHINE SPEED: 15 CPM

PRELIMINARY
 (ALL DIMENSIONS ARE APPROXIMATE AND MAY VARY WITH FINAL DESIGN)

PROPRIETARY
 NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED THEREIN MAY BE REPRODUCED OR DISCLOSED TO ANYONE WITHOUT THE WRITTEN PERMISSION OF R.A. PEARSON CO.

DATE	REVISION	ECN NO.	REV. BY	CHKD BY
06/12/24	MOTOR UPDATE, 3PH		SFC	SFC
10/8/20	TAPE HEAD UPDATE		SFC	

2' - 2 7/16" 672

DIMENSIONS ARE IN FOOT FRACTION INCH OVER MILLIMETERS.

PEARSON
 MEASURING SYSTEMS
 4125 WEST SUNSET HIGHWAY
 SPOKANE, WASHINGTON 99224
 WWW.PEARSONPKG.COM

TITLE: CS15-29T CASE SEALER

DR.	SFC	10/7/20	DWG NO.	D624540R-4
CHK.			SCALE	SHEET
APP.				