CORRUGATED SIZE RANGE


ERECTED CASE SIZE

CASE	LENGTH	WIDTH	DEPTH	OPEN DEPTH
MINIMUM	8.00 (203)	5.50 (140)	3.00 (76)	5.75 (146)
MAXIMUM	20.00 (508)	14.00 (355)	14.00 (355)	19.00 (482)

SET-UP CASE

KNOCKDOWN CASE SIZES (IN)

	KDL	KDW	FLAP
MINIMUM	13.50 (343)	8.50 (216)	2.75 (70)
MAXIMUM	32.00 (812)	26.00 (660)	7.00 (177)



UTILITY REQUIREMENTS

AIR REQUIREMENTS: 1.2 SCF/CYCLE @ 80 PSI (0.038m PER CYCLE @ 551.2 KPa) ELECTRICAL REQUIREMENTS: 460 VOLTS, 3 PHASE, 60 Hz STANDARD


> FULL LOAD AMPS - 10 AMPS DISCONNECT SIZE - 30 AMP


POWER REQUIREMENTS PROVIDED ARE FOR A BASE MACHINE AND CUSTOM

OPTIONS MAY RESULT IN CHANGES.

MACHINE WEIGHT: APPROX. 2000 LBS. (907 Kg.)

SPEED CAPACITY: MAXIMUM 15 CASES PER MINUTE






OPEN


DEPTH (O.D.

DOUBLE POINT SCORING

THE STYLE AND QUALITY OF SCORING CAN EFFECT THE OPERATION AND PERFORMANCE OF THE CE25-T.

PEARSON PACKAGING SYSTEMS RECOMMENDS THAT CASES WITH DOUBLE POINT SCORING BE USED. (SEE SKETCH ABOVE) IN ORDER TO MAXIMIZE THE CONSISTENCY OF OPERATION OF YOUR MACHINE.





MACHINE SHOWN RUNS RH CASES

PRELIMINARY

ALL DIMENSIONS ARE APPROXIMATE AND MAY VARY WITH FINAL DESIGN

PROPRIETARY NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED THERIN PERMISSION OF R.A. PEARSON CO.

